

# Fluid Pump TWS 600

## Pump Truck Details

- Mercedes Actros V8 diesel engine with 550 BHP & Allison gear box.
- The truck is built on a 6x6 rigid chassis for easy access in remote areas.
- The truck is purpose built for operating in extreme environments such as desert & cold areas (-40°C & 50°C).
- Unit has a trailer attached mobile 2 x 15 m<sup>3</sup> storage tank which can remain on the trailer during operations.
- Storage tank has mixing and fill lines incorporated and is approved for storing corrosive fluids on location.



## Fluid Pump

- Unit is built with an API spec SPM TWS 600 pump.
- The truck engine gear- box drives The Pump fluid-end via the PTO.
- The Fluid-end is set-up with 3 1/2" plungers capable of pumping 1500 lt/min @ 100 bar.
- The max. allowable operating pressure is of 700 bar.
- The unit is equipped with 2 sets of Mission Centrifugal Pumps to boost the fluid-end and filling the mixing tank.
- The 2 x 3m<sup>3</sup> Mixtank is equipped with electronic level controls and paddle for mixing brines & fluids.
- The trailer mounted 2 compartment storetank is able to carry 30m<sup>3</sup> of fluids and is self-supported.



## Certification

- T.U.V.
- ADR & RDW

Pump	Truck	Trailer
<b>Width:</b>	2.50 mtr	2.50 mtr
<b>Length:</b>	12.00 mtr	6.50 mtr
<b>Height:</b>	4.00 mtr	3.80 mtr
<b>Weight:</b>	16.000 kg	9.000 kg

The pump is completed with 30 mtr 2" weco 1502 Treating iron & low pressure equipment.



**WSG**<sup>®</sup>

Well Services Group

### WSG Coil Services bv

Phileas Foggstraat 65

NL-7825 AL EMMEN

The Netherlands

Phone +31 591 66 81 55

Fax +31 591 66 81 50

info@wellservices-group.com

www.wellservices-group.com

'best in class'