



WSG[®]

Well Services Group

WSG Coil Services bv

Phileas Foggstraat 65

NL-7825 AL EMMEN

The Netherlands

Phone +31 591 66 81 55

Fax +31 591 66 81 50

info@wellservices-group.com

www.wellservices-group.com

‘best in class’

Injector Head HR 680

Injector Head Details:

- Coil Services utilizes the latest types of Coiled Tubing injectors (Hydra-Rig) available to the market.
- Including a stabbing winch for easy and safe control when inserting the Coiled Tubing minimizing climbing and reducing Rig-up time.
- Designed for 80.000 lbs of continuous pull and 40.000 lbs snubbing capacity.
- Designed to run sizes from 1 ¼" up to 3 ½" Coiled Tubing.
- Variable Gearbox ensuring smooth ROP & speed control for UBD and other speed applications.
- Easy change of gripper inserts in case "Quick connect" 5 seconds to remove or install gripper blocks).
- Hardened and grooved single piece grippers to avoid "slipping" from pipe
- Depending on size Coiled Tubing either to be ran with a 72" or a 100" gooseneck.
- Electronic load cell.
- Injector installed with Dual spring pressure released brake system.

Certification

- Built according to: ATEX, DNV 2.7-1 and EN12079.

Dimensions

Injector head	HR 680
Width:	1.32 mtr
Length:	1.40 mtr
Height:	2.40 mtr
Weight	4.500 kg

