

Coiled Tubing Tower

Support Tower Details

- Hydraulic adjustable Bottom & Top section 5 x Middle sections Total height 22 mtr.
- Self-elevating hydraulic lifted guards & railings.
- Top section work floor hydraulic adjustable (incl. injector-head) in height, length and side-ways motion.
- Tower stacking by Inter frame container twist locks.
- Fast rig-up all hydraulic.
- No trip hazards.
- Maximum climbing height in middle sections 2.5 mtr.
- Safe working area for operator at all times.
- Fall Shute Gin poles for fast & safe emergency abandoning.
- No crane required once Rugged-up.



Certification

- Certified by Bureau Veritas.
- EN12079.
- DNV 2.7-1.
- T.U.V.
- Berg Ambt



Dimensions

| | Top Section |
|-------------------|-------------|
| Width: | 2.50 mtr |
| Length: | 4.50 mtr |
| Height transport: | 2.60 mtr |
| Height max: | 3.60 mtr |
| Weight: | 10.000 kg |



| | Middle sections |
|---------|-----------------|
| Width: | 2.40 mtr |
| Length: | 2.70 mtr |
| Height: | 2.60 mtr |
| Weight: | 2.500 kg |



| | Bottom section |
|-------------------|----------------|
| Width: | 2.50 mtr |
| Length: | 8.50 mtr |
| Height transport: | 3.09 mtr |
| Height max: | 5.20 mtr |
| Weight: | 11.500 kg |



WSG Coil Services bv

Phileas Foggstraat 65

NL-7825 AL EMMEN

The Netherlands

Phone +31 591 66 81 55

Fax +31 591 66 81 50

info@wellservices-group.com

www.wellservices-group.com

'best in class'