

Slickline Unit

Slickline Unit Details

- The wireline unit is built according the latest requirements for on- and offshore use.
- The wireline unit is driven by an Iveco diesel engine with 79 HP and equipped with Zone II exhaust cooling and engine shutdown systems.
- The wireline unit is noise level tested according ISO 3746. Acoustic enclosure level rated for 80 dBA.
- The wireline unit is equipped with a smart monitor/display for data acquisition and hydraulic limit control to avoid over-pull.
- Double wire Drum possibilities for standard or heavy duty applications.

Certification

Certified to:

- EN12079
- DNV 2.7-1.
- SI 289
- TUV

Wire Capabilities

Dimensions

| Wires | Max Pull # |
|------------------------------|------------|
| 0.125" GD22 | 1600# |
| 0.160" GD22 | 2460# |
| | |
| | |

| | Transport frame |
|-----------------------|-----------------|
| Width: | 1.35 mtr |
| Length: | 3.34 mtr |
| Height: | 2.60 mtr |
| Weight: | 4.700 kg |
| Excluding winch drums | |



WSG[®]

Well Services Group

WSG Slickline Services bv

Phileas Foggstraat 65

NL-7825 AL EMMEN

The Netherlands

Phone +31 591 66 81 55

Fax +31 591 66 81 50

info@wellservices-group.com

www.wellservices-group.com

'best in class'